

Latour

Product information:

The Latour and Latour Stripes ranges offer durability, functionality and design. The ranges can be used alone or can work together to create interesting and unique floor schemes. Latour and Latour Stripes are suitable for a wide variety of commercial and educational environments.



Warranties:

10 year wear warranty
 10 year anti-static warranty
 Full warranty details available on request



BRE Global (BREEAM):

'A+' Commercial Office (tile)
 'A+' Education (tile)
 'A+' Healthcare (tile)

Specification:

Product Form	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Loop Pile
Surface Yarn	100% Meraklon BCF Polypropylene
Dye Method	Solution Dyed
Total Carpet Weight	4400 g/m ²
Tufted Pile Weight	543 g/m ²
Gauge	39.4 per dm
Stitches	39.4 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	6.8mm

Performance Specification

Static Electricity ISO 6356 <2kV

Flammability

BSEN 13501-1 Class Efl-s1


For recommended adhesives contact Technical Services on 01625 428922.



Latour




Broadloom



Quarter Turn

Latour Stripes



Must be laid Quarter Turn



ISO 9001 : FM 10763
 ISO 14001 : EMS 59511



BS OHSAS 18001
 IV 18/18493

16195

GRADUS

Gradus Carpets Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 859000 Fax: 01625 850352

For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

www.gradusworld.com